



PUMP

The GRUNDFOS CR pump range are of vertical multistage in-line centrifugal design suitable for a wide range of water supply, irrigation, liquid transfer and boosting applications. The pumps are of heavy duty construction and are designed for continuous duty in commercial and industrial installations. All vital components including the impellers, intermediate chambers and shaft are made from stainless steel and the top and bottom housings from cast iron. The pump is water lubricated and is provided with a tungsten carbide faced mechanical shaft seal.

For aggressive liquids the 'N' version is available which features stainless steel top and bottom pump housings.

MOTOR

The pumps are coupled to high efficiency 'Blue flux' totally enclosed fan cooled 2-pole GRUNDFOS motors complying with IEC & DIN standards. All motors must be connected to an effective motor starter in accordance with local regulations.

Enclosure Class: IP55 **Insulation Class:** F **Voltage:** 3 x 415V **Speed:** 2900 rpm

OPERATING CONDITIONS

Pumped liquids: Thin, clean, non-aggressive and non-explosive liquids without solid particles or fibres.

Liquid Temperature Range: - 30°C to +120°C

Max Ambient Temperature: +60°C

Max Suction Lift: According to the NPSH curve plus a safety margin of 1 m.

Max Operating Pressure: Models up to CR 32-6 - 16 Bar, CR 32-8 and CR 32-12 - 25 Bar

PUMP DATA

Model	Motor		Full Load Current (A)	I start
	kW	HP		
CR 32-2	4.0	5.5	8.0	12.3
CR 32-3	5.5	7.5	11.2	11.7
CR 32-4	7.5	10.0	15.2	11.1
CR 32-6	11.0	15.0	21.4	8.0
CR 32-8	15.0	20.0	26.5	7.0
CR 32-10	18.5	25.0	31.5	7.0
CR 32-12	22.0	30.0	38.5	7.2
CR 32-14	30.0	40.0	53	7.0

Model	Dimensions (mm)						Weight (kg)
	B ₁	B ₂	B ₁ +B ₂	D ₁	D ₂	D ₃	
CR 32-2	575	372	947	220	134	158	82
CR 32-3	645	391	1036	220	134	298	96
CR 32-4	715	391	1106	220	134	298	101
CR 32-6	965	499	1464	260	172	350	142
CR 32-8	1105	478	1583	320	197	350	169
CR 32-10	1245	518	1763	320	197	350	183
CR 32-12	1385	610	1995	363	262	350	276
CR 32-14	1525	646	2171	415	300	400	332

