



The Dayliff Drytek Electronic Pump Controller is a solid state integrated control unit for all types of pumps with a particular application to borehole installations. Panels are fitted with a digital display of both operating and fault parameters and settings are simply made using fascia mounted push buttons. A range of sizes are available for single and three phase motors, settings for particular motor sizes being effected by simple adjustment of the running current.

Features

- Incoming mains isolator switch with fuse protection and door interlock.
- Digital display of motor operating status including voltage, amps, cos Ø and fault messages.
- Protection against over/under voltage, motor overload and phase sequence/loss.
- Electronic dry run protection using cos Ø sensitivity adjustment dispensing with the need for low level electrodes and cables.
- Selectable auto/manual operation with an extra terminal set for an additional external control function, e.g float switch or pressure switch.
- Auto restart for fault signals with 4 separate adjustable times from 0-250 mins.
- Large IP55 rated flame-proof plastic enclosure with space for additional accessories as may be specified.

Dayliff Drytek Electronic Pump Controllers are high specification units that provide comprehensive protection for all pump motors. The combination of extensive built-in functionality that eliminates the need for expensive separate components, a wide application range through easy adjustment and simple operation provides units of great versatility and effectiveness. These features combined with exceptional value results in one of the best pump controllers available.

Enclosure Class: IP55

Temperature Range: -5° to +40°C

Power Supply: 240V±10% / 415V±10%

General Data

Controller Model	Power (kW)		Current Range (A)	Dimensions (mm) LxWxH	Weight (kg)
	Min	Max			
DRYTEK 1Ph/2.2kW	0.37	2.2	2-18	340x240x170	1.5
DRYTEK 3Ph/7.5kW	0.55	7.5	2-16	340x240x170	2.5
DRYTEK 3Ph/15kW	7.5	15	16-30	340x240x170	3.5