



Dayliff Paneltim swimming pools are stylish rectangular packaged pools suitable for above ground or in-ground installation. The structure is fabricated from light 50 mm Paneltim polypropylene sandwich panels in grey/offwhite colour welded and bound together to make a strong, leakproof and long lasting structure. They are supplied completely prefabricated ex-factory for simple and quick installation on a light concrete screed base. Features include:-

- Available in four standard lengths with width and depth options as indicated
- Standard specification is Freeboard configuration with skimmer. Decklevel type with peripheral grille covered drain channel is available as an option
- Supplied complete with fitted skimmers, inlets and side main outlet
- Available with complete water circulation equipment package including reliable Dayliff circulation pump and filter plus extras of lights, heaters and other poolside accessories
- Inbuilt steps or external tubular step ladder offered to choice

Dayliff Paneltim pools give installation flexibility and guaranteed long life and are a strong, robust and cost effective solution for all smaller domestic swimming pool installations.

Pool Description	Pool Volume (m³)								Filter	Pump
	Width(m)	3.0		3.6		4.8				
	Length\Depth(m)	1.2	1.5	1.2	1.5	1.2	1.5			
PP 5	4.8	17	22	21	26	28	35	DX300	DPL550	
PP 7	7.4	27	33	32	40	43	53			
PP10	10.	36	45	43	54	58	72	DX500		
PP12	11.6	42	52	50	63	67	84			

Notes on additional fittings:

- Standard pool type is Freeboard. Deck level or infinity will have additional cost.
- Steps will be standard with an option of bench at additional cost.
- Inlets, suction, skimmer and lights are exclusive of the shell price