



Solar pumping is now firmly established as the technology for water supply in remote off-grid applications and also as the costs reduce increasingly for general pumping duties. Dayliff have been leaders in the technology since the birth of the industry and today offer a wide range of options for every solar pumping requirement imaginable. Particularly a range of competitive, high specification solar pumping systems have been developed for smaller scale applications which are based on robust submersible solar pumps specially designed for PV powered water supply from wells and boreholes.

Together with the pump all systems include:-

- The appropriate specifications and number of Grade 1 PV modules with connectors for simplified installation
- Submersible drop cable and joint together with 10m module connection cable
- DC solar isolator with MCB control provided for module isolation
- Safety rope and HDPE pipe connectors

Module supports and piping are not included. The various systems offered give a wide range of duties, indicative performance being given. Full details of pump performance and specification is given in the Dayliff Product Manual and should be referred to when selecting equipment.

SUNFLO-S	SUNFLO-A	SUNFLO-B
<p>Positive displacement type of three chamber diaphragm design. They are manufactured from high quality engineering plastics with plastic casings for the 150 model and stainless steel for the 300. Pumps can be connected directly to a 24V PV power supply for daytime only pumping or through a charge controller connected to batteries for extended daily operation.</p>	<p>All models are of helical rotary screw stainless steel design for high efficiency and feature an inbuilt controller that gives operating protection for direct connection to the PV modules. All models are of narrow 3" diameter specifically designed for boreholes.</p>	<p>Higher specification pumps of both helical rotor and centrifugal type that are provided with separate controllers that feature MPPT technology to maximise output as well as electrical protection and giving operating status. connection is also extended daily providing indicator lights Battery available for pumping.</p>

System Options

Pump Model	Indicative Performance	Input Voltage (V)	Motor Rating Watts	Peak Voltage (V)	Open Circuit Voltage (VoC)	PV Modules	Cable length, 2.5mm ²	Outlet Size
SUNFLO-S 150	1m ³ /day at 30m	24	120	24	<50	1x200W	30m	1/2"
SUNFLO-S 300	3m ³ /day at 60m	24	300	24	<50	2x200W	60m	3/4"
SUNFLO-A 150H	2m ³ /day at 30m	24	150	≥30	<50	1x200W	30m	3/4"
SUNFLO-A 270H	3m ³ /day at 50m	36	270	≥45	<100	2x200W	50m	3/4"
SUNFLO-A 600H	4m ³ /day at 70m	48	600	≥60	<100	4x200W	70m	3/4"
SUNFLO-B 120H	3m ³ /day at 30m	24	120	≥30	<50	1x200W	30m	3/4"
SUNFLO-B 500C	6m ³ /day at 40m	48	500	≥60	<100	4x200W	40m	1"
SUNFLO-B 1000C	12m ³ /day at 70m	110	1000	≥112	<200	8x200W	70m	1 1/4"

Note1: Greater water outputs will be available at lower heads

Note2: Actual performance will be determined by site conditions and irradiation levels.